


# MBN1200E17D

Silicon N-channel IGBT


## FEATURES

- \* High speed, low loss IGBT module.
- \* Low driving power due to low input capacitance MOS gate.
- \* Low noise due to ultra soft fast recovery diode.
- \* High reliability, high durability module.
- \* High thermal fatigue durability.  
( $\Delta T_c=70^\circ\text{C}$ ,  $N>30,000$ cycles)
- \* Isolated heat sink (terminal to base).

## CIRCUIT DIAGRAM



## OUTLINE DRAWING



## ABSOLUTE MAXIMUM RATINGS ( $T_c=25^\circ\text{C}$ )

Item	Symbol	Unit	MBN1200E17D
Collector Emitter Voltage	$V_{CES}$	V	1,700
Gate Emitter Voltage	$V_{GES}$	V	$\pm 20$
Collector Current	DC	$I_C$	1,200
	1ms	$I_{CP}$	2,400
Forward Current	DC	$I_F$	1,200
	1ms	$I_{FM}$	2,400
Junction Temperature	$T_j$	$^\circ\text{C}$	-40 ~ +125
Storage Temperature	$T_{stg}$	$^\circ\text{C}$	-40 ~ +125
Isolation Voltage	$V_{ISO}$	$V_{RMS}$	4,000(AC 1 minute)
Screw Torque	Terminals (M4/M8)	-	2/10 (1)
	Mounting (M6)	-	6 (2)

Notes: (1) Recommended Value  $1.8\pm 0.2/9\pm 1\text{N}\cdot\text{m}$ (2) Recommended Value  $5.5\pm 0.5\text{N}\cdot\text{m}$ 

## ELECTRICAL CHARACTERISTICS

Item	Symbol	Unit	Min.	Typ.	Max.	Test Conditions
Collector Emitter Cut-Off Current	$I_{CES}$	mA	-	-	10	$V_{CE}=1,700\text{V}$ , $V_{GE}=0\text{V}$ , $T_j=25^\circ\text{C}$
			-	10	35	$V_{CE}=1,700\text{V}$ , $V_{GE}=0\text{V}$ , $T_j=125^\circ\text{C}$
Gate Emitter Leakage Current	$I_{GES}$	nA	-500	-	+500	$V_{GE}=\pm 20\text{V}$ , $V_{CE}=0\text{V}$ , $T_j=25^\circ\text{C}$
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	V	2.0	2.7	3.3	$I_C=1,200\text{A}$ , $V_{GE}=15\text{V}$ , $T_j=125^\circ\text{C}$
Gate Emitter Threshold Voltage	$V_{GE(TO)}$	V	5.0	6.5	8.0	$V_{CE}=10\text{V}$ , $I_C=120\text{mA}$ , $T_j=25^\circ\text{C}$
Input Capacitance	$C_{ies}$	nF	-	100	-	$V_{CE}=10\text{V}$ , $V_{GE}=0\text{V}$ , $f=100\text{kHz}$ , $T_j=25^\circ\text{C}$
Internal Gate Resistance	$R_{ge}$	$\Omega$	-	0.8	-	$V_{CE}=10\text{V}$ , $V_{GE}=0\text{V}$ , $f=100\text{kHz}$ , $T_j=25^\circ\text{C}$
Switching Times	Rise Time	$t_r$	-	0.6	1.0	$V_{CC}=900\text{V}$ , $I_C=1,200\text{A}$ $L=65\text{nH}$ , $C_{GE}=120\text{nF}$ (TBD) (3) $R_G=1.5\Omega$ (TBD) (3) $V_{GE}=\pm 15\text{V}$ , $T_j=125^\circ\text{C}$
	Turn On Time	$t_{on}$	-	0.9	1.8	
	Fall Time	$t_f$	-	0.3	0.7	
	Turn Off Time	$t_{off}$	-	1.4	3.4	
Peak Forward Voltage Drop	$V_{FM}$	V	1.3	1.9	2.5	$I_F=1,200\text{A}$ , $V_{GE}=0\text{V}$ , $T_j=125^\circ\text{C}$
Reverse Recovery Time	$t_{rr}$	$\mu\text{s}$	-	0.5	1.0	$V_{CC}=900\text{V}$ , $I_C=I_F=1,200\text{A}$
Turn On Loss	$E_{on(10\%)}$	J/P	0.09	0.25	0.4	$L=65\text{nH}$ , $C_{GE}=120\text{nF}$ (TBD) (3)
Turn Off Loss	$E_{off(10\%)}$	J/P	0.18	0.35	0.5	$R_G=1.5\Omega$ (TBD) (3)
Reverse Recovery Loss	$E_{rr(10\%)}$	J/P	0.18	0.4	0.6	$V_{GE}=\pm 15\text{V}$ , $T_j=125^\circ\text{C}$
Stray inductance module	$L_{SCE}$	nH	-	18	-	
Thermal Impedance	IGBT	$R_{th(j-c)}$	-	-	0.018	Junction to case
	FWD	$R_{th(j-c)}$	-	-	0.030	
Contact Thermal Impedance		$R_{th(c-f)}$	-	0.008	-	Case to fin

Notes:(3)  $R_G$  and  $C_{GE}$  value is the test condition's value for evaluation of the switching times, not recommended value.Please, determine the suitable  $R_G$  and  $C_{GE}$  value after the measurement of switching waveforms (overshoot voltage, etc.) with appliance mounted.

\* Please contact our representatives at order.

\* For improvement, specifications are subject to change without notice.

\* For actual application, please confirm this spec sheet is the newest revision.

# MBN1200E17D

## DEFINITION OF TEST CIRCUIT




Fig.1 Switching test circuit




Fig.2 Definition of stray inductance





Fig.3 Definition of switching loss

# MBN1200E17D


## 1. STATIC CHARACTERISTICS

TYPICAL




Collector Current vs. Collector to Emitter Voltage

TYPICAL



Collector Current vs. Collector to Emitter Voltage


TYPICAL




Forward Voltage of free-wheeling diode

# MBN1200E17D


## 2. DYNAMIC CHARACTERISTICS




Turn-on Loss vs. Collector Current



Turn-off Loss vs. Collector Current




Recovery Loss vs. Forward Current




Switching Time vs. Collector Current


# MBN1200E17D



Turn-on Loss vs. Gate Resistance




Turn-off Loss vs. Gate Resistance



Recovery Loss vs. Gate Resistance

# MBN1200E17D

## 3. TRANSIENT THERMAL IMPEDANCE



## 4. Negative environmental impact material

Please note that following materials are contained in the product In order to keep characteristics and reliability level.

Material	Contained part
Lead (Pb) and its compounds	Solder
Arsenic and its compounds	Si chip

# MBN1200E17D

## HITACHI POWER SEMICONDUCTORS

### Notices

1. The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact Hitachi sales department for the latest version of this data sheets.
2. Please be sure to read "Precautions for Safe Use and Notices" in the individual brochure before use.
3. In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, life-support-related medical equipment, fuel control equipment and various kinds of safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement. Or consult Hitachi's sales department staff.
4. In no event shall Hitachi be liable for any damages that may result from an accident or any other cause during operation of the user's units according to this data sheets. Hitachi assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in this data sheets.
5. In no event shall Hitachi be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
6. No license is granted by this data sheets under any patents or other rights of any third party or Hitachi, Ltd.
7. This data sheets may not be reproduced or duplicated, in any form, in whole or in part, without the expressed written permission of Hitachi, Ltd.
8. The products (technologies) described in this data sheets are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety not are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.

- 
- For inquiries relating to the products, please contact nearest overseas representatives that is located "Inquiry" portion on the top page of a home page.
- 

Hitachi power semiconductor home page address <http://www.hitachi.co.jp/products/power/pse/>